KERN MPE 250K100PM



High quality personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional



Category	
Brand	KERN
Product categoriy	Medical scale
Product group	Personal floor scale
Product family	MPE
Measuring System	

Measuring System	
Conformity assessment possible	\checkmark
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	250 kg
Readability [d]	0,1 kg
Resolution	2.500
Linearity	± 0,1 kg
Reproducibility	0,1 kg
Tare range	-249,9 kg
Default unit	kg
Units	kg
Units (if device is conformity assessed)	kg
Minimum weight [Min]	2 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	200 kg (M1)
Stabilization time	3 s
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg

\ \

Approval

CE mark	
Pattern approval for conformity	
assessment	

Accuracy classe	III
Verification scale interval [e]	0,1 kg
Conformity assessment possible ex works	1
Approval according to 93/42/EEC (med.)	1
Display	
Display type	LCD
Display backlight	✓
Display digit height - smallest digit	2 mm
Display digit height	25 mm
Languages of the user interface	Symbol language
Construction	
Dimension display device (W×D×H)	200×55×128 mm
Dimensions weighing platform (W×D×H)	365×360×80 mm
Dimensions completely mounted (W×D×H)	365×570×1030 mm
Material display housing	Plastics
Material housing	steel, lacquered
Material weighing plate	plastic
Dimensions weighing surface (W×D)	327×333 mm
Transport wheels	✓
Stand height	940 mm
Functions	
Number of keys for operation	7
	5 min
Auto-off interval(s) in mains power	30 min
mode	selectable 15 min
	3 min
Auto-off interval(s) in battery	5 min
mode/rechargeable battery mode	30 min
	15 min
PreTare function	✓
Tare function	manual (single & multi)
Hold function	1
Function for averaging under unstable weighing conditions	✓
Function for BMI calculation	1
Interfaces	RS-232 standard
Power Supply	
Input voltage power supply / power [Max]	100 V - 240 V, 50 / 60 Hz
	1

KERN MPE 250K100PM



High quality personal floor scale with BMI function – with approval for professional medical use in medical diagnostics, verification optional

Input voltage device / power [Max]	12 V, 500 mA
Plug-in power supply type	Power adapter
Supplied power supply	Power supply & battery function (battery not included)
Plug-in power supply / adapter for countries - included with the delivery	EURO UK CH
Plug-in power supply / adapter for countries - optional	EURO
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Battery	6×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Battery insert
Battery operating time	20 h

Environmental conditions

Humity of environment [Max]	80 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	1010×290×445 mm
Net weight	11,26 kg
Shipping method	Parcel service
Net weight approx.	12 kg
Gross weight approx.	14 kg
Shipping weight	26,1 kg

Services (optional)

Article number for adjustment at	961-249
the location of installation	901-249
Auticle, number for confermity	
Article number for conformity	965-129
assessment	,00 12,
Article number for DAkkS	
	963-129
calibration	
Article number for certificate of	
	969-517
conformity (verification)	

Pictograms

STANDARD



OPTION

	DAkkS
ACCU	+3 DAYS

FACTORY

