KERN MWA 300K-1M



Wheelchair platform scale with two integrated access ramps for easy access – with approval for professional medical use in medical diagnostics, verification optional



Category

Brand	KERN
Product categoriy	Medical scale
Product group	Wheelchair platform scale
Product family	MWA

Measuring System

Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	300 kg
Readability [d]	0,1 kg
Resolution	3.000
Linearity	± 0,1 kg
Reproducibility	0,1 kg
Tare range	-299,9 kg
Default unit	kg
Units	kg
Units (if device is conformity assessed)	kg
Minimum weight [Min]	2 kg
Adjustment options	Adjusting with external weight
Recommended adjusting weight	300 kg (M1)
Warm-up time	10 min
Eccentric loading at 1/3 [Max]	0,1 kg

Approval

CE mark	1
Accuracy classe	III
Verification scale interval [e]	0,1 kg
Conformity assessment possible ex works	✓
Approval according to 93/42/EEC (med.)	1

Display	
Display type	LCD
Display backlight	\checkmark
Display digit height - smallest digit	5 mm
Display digit height	25 mm
Languages of the user interface	Symbol language
Construction	
Dimension display device (W×D×H)	200×130×60 mm
Dimensions weighing platform (W×D×H)	995×945×40 mm
Dimensions completely mounted (W×D×H)	1180×1130×90 mm
Material display housing	Plastics
Material housing	steel, lacquered
Material weighing plate	steel, lacquered
Dimensions weighing surface (W×D)	880×840 mm
Display device cable length	3 m
Wall mount	1
Stand height	940 mm
Functions	
Number of keys for operation	6
Number of keys for operation	0
Number of keys for operation	3 min
Auto-off interval(s) in battery	3 min 5 min
	3 min 5 min 30 min
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min 5 min 30 min 15 min
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function	3 min 5 min 30 min 15 min manual (single & multi)
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function	3 min 5 min 30 min 15 min
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function	3 min 5 min 30 min 15 min manual (single & multi)
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under	3 min 5 min 30 min 15 min manual (single & multi)
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions	3 min 5 min 30 min 15 min manual (single & multi) ✓
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation	3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces	3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓ ✓ RS-232 standard
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces IP protection - load cell	3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓ ✓ RS-232 standard
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces IP protection - load cell Power Supply Input voltage power supply /	3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓ ✓ RS-232 standard IP65 100 V - 240 V, 50 / 60
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces IP protection - load cell Power Supply Input voltage power supply / power [Max]	3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓ S-232 standard IP65 I00 V - 240 V, 50 / 60 Hz
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces IP protection - load cell Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max]	3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓ ✓ RS-232 standard IP65 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter Power supply & battery function (battery not
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces IP protection - load cell Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type	3 min 5 min 30 min 15 min manual (single & multi) \checkmark \checkmark RS-232 standard IP65 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter Power supply & battery
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces IP protection - load cell Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply type	3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓ ✓ ✓ S-232 standard IP65 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter Power supply & battery function (battery not included)
Auto-off interval(s) in battery mode/rechargeable battery mode Tare function Hold function Function for averaging under unstable weighing conditions Function for BMI calculation Interfaces IP protection - load cell Power Supply Input voltage power supply / power [Max] Input voltage device / power [Max] Plug-in power supply Plug-in power supply	3 min 5 min 30 min 15 min manual (single & multi) ✓ ✓ ✓ S-232 standard IP65 100 V - 240 V, 50 / 60 Hz 12 V, 500 mA Power adapter Power supply & battery function (battery not included) EURO

KERN MWA 300K-1M



Wheelchair platform scale with two integrated access ramps for easy access – with approval for professional medical use in medical diagnostics, verification optional

Plug-in power supply / adapter for countries - optional	EURO AUS UK US CH
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	12 h
Rechargeable battery operating time - backlight on	20 h
Rechargeable battery operating time - backlight off	40 h
Battery	6×1.5 V AA
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Battery insert
Battery operating time	20 h

Environmental conditions

Humity of environment [Min]	5 %
Humity of environment [Max]	80 %
Ambient temperature [Min]	10 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

Packing & Shipping

Readability force [d] (N)	2 d
Dimensions packaging (W×D×H)	1255×1100×285 mm
Net weight	68 kg
Shipping method	Freight
Net weight approx.	70 kg
Gross weight approx.	80 kg
Shipping weight	80 kg

Services (optional)

Article number for adjustment at the location of installation	961-249
Article number for conformity assessment	965-129
Article number for DAkkS calibration	963-129
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD



OPTION

	DAkkS
ACCU	+3 DAYS

FACTORY

